

IPOTEC

Innovation in Polymer Technology

Ipotec LLC, 41 Industrial Drive, Exeter, NH 03833, USA

Tel: (+1)(603) 778 2882 • Fax: (+1)(603) 778 2878 • <http://www.ipotec.com> • e-mail: info@ipotec.com

GS-N5 Silicone Rubber Coated Fiberglass Slewing

Standard Sizes

Size	Inside Diameter, inches (mm)		Standard Pack
	Max.	Min.	
# 24	0.027 (0.69)	0.020 (0.51)	500 ft spool
# 22	0.032 (0.81)	0.025 (0.64)	500 ft spool
# 20	0.039 (0.99)	0.032 (0.81)	500 ft spool
# 19	0.044 (1.12)	0.036 (0.91)	500 ft spool
# 18	0.049 (1.24)	0.040 (1.02)	500 ft spool
# 17	0.054 (1.37)	0.045 (1.14)	500 ft spool
# 16	0.061 (1.55)	0.051 (1.30)	500 ft spool
# 15	0.067 (1.70)	0.057 (1.45)	500 ft spool
# 14	0.074 (1.88)	0.064 (1.63)	500 ft spool
# 13	0.082 (2.08)	0.072 (1.83)	250 ft spool
# 12	0.091 (2.31)	0.081 (2.06)	250 ft spool
# 11	0.101 (2.60)	0.091 (2.31)	250 ft spool
# 10	0.112 (2.80)	0.102 (2.60)	250 ft spool
# 9	0.124 (3.10)	0.114 (2.90)	250 ft spool
# 8	0.141 (3.60)	0.129 (3.30)	250 ft spool
# 7	0.158 (4.00)	0.144 (3.70)	250 ft spool
# 6	0.178 (4.50)	0.162 (4.10)	150 ft spool
# 5	0.198 (5.00)	0.182 (4.60)	150 ft spool
# 4	0.224 (5.70)	0.204 (5.20)	150 ft spool
# 3	0.249 (6.30)	0.229 (5.80)	150 ft spool
# 2	0.278 (7.10)	0.258 (6.60)	150 ft spool
# 1	0.311 (7.90)	0.289 (7.30)	100 ft coil
# 0	0.347 (8.80)	0.325 (8.30)	100 ft coil
3/8 in.	0.399 (10.1)	0.375 (9.50)	100 ft coil
7/16 in.	0.462 (11.7)	0.438 (11.1)	100 ft coil
1/2 in.	0.524 (13.3)	0.500 (12.7)	100 ft coil
5/8 in.	0.655 (16.6)	0.625 (15.9)	50 ft coil
3/4 in.	0.786 (20.0)	0.750 (19.1)	50 ft coil
7/8 in.	0.911 (23.1)	0.875 (22.2)	50 ft coil
1 in.	1.036 (26.3)	1.000 (25.4)	50 ft coil

Wall Thickness Grade A: 0.040 +/- 0.016 inch (1.0 +/- 0.4mm)

Grade B: 0.031 +/- 0.016 inch (0.8 +/- 0.4mm)

Grade C: 0.028 +/- 0.016 inch (0.7 +/- 0.4mm)

Applies only to sizes under 1/2in.

Slewing 1/2in and above may have thicker wall.