

IPOTEC

Innovation in Polymer Technology

Ipotec LLC, 41 Industrial Drive, Exeter, NH 03833, USA
Tel: (+1) (603) 778 2882 • Fax: (+1) (603) 778 2878 • <http://www.ipotec.com> • e-mail: info@ipotec.com

GS-N5 Silicone Rubber Coated Fiberglass Sleeving

Standard Sizes

Sold in continuous coils as produced or in standard pack sizes shown below, on request

Size	Inside Diameter, inches (mm)		Available Pack on Request
	Max.	Min.	
# 24	0.027 (0.69)	0.020 (0.51)	500 ft spool / coil
# 22	0.032 (0.81)	0.025 (0.64)	500 ft spool / coil
# 20	0.039 (0.99)	0.032 (0.81)	500 ft spool / coil
# 19	0.044 (1.12)	0.036 (0.91)	500 ft spool / coil
# 18	0.049 (1.24)	0.040 (1.02)	500 ft spool / coil
# 17	0.054 (1.37)	0.045 (1.14)	500 ft spool / coil
# 16	0.061 (1.55)	0.051 (1.30)	500 ft spool / coil
# 15	0.067 (1.70)	0.057 (1.45)	500 ft spool / coil
# 14	0.074 (1.88)	0.064 (1.63)	500 ft spool / coil
# 13	0.082 (2.08)	0.072 (1.83)	250 ft spool / coil
# 12	0.091 (2.31)	0.081 (2.06)	250 ft spool / coil
# 11	0.101 (2.60)	0.091 (2.31)	250 ft spool / coil
# 10	0.112 (2.80)	0.102 (2.60)	250 ft spool / coil
# 9	0.124 (3.10)	0.114 (2.90)	250 ft spool / coil
# 8	0.141 (3.60)	0.129 (3.30)	250 ft spool / coil
# 7	0.158 (4.00)	0.144 (3.70)	250 ft spool / coil
# 6	0.178 (4.50)	0.162 (4.10)	150 ft spool / coil
# 5	0.198 (5.00)	0.182 (4.60)	150 ft spool / coil
# 4	0.224 (5.70)	0.204 (5.20)	150 ft spool / coil
# 3	0.249 (6.30)	0.229 (5.80)	150 ft spool / coil
# 2	0.278 (7.10)	0.258 (6.60)	150 ft spool / coil
# 1	0.311 (7.90)	0.289 (7.30)	100 ft coil
# 0	0.347 (8.80)	0.325 (8.30)	100 ft coil
3/8 in.	0.399 (10.1)	0.375 (9.50)	100 ft coil
7/16 in.	0.462 (11.7)	0.438 (11.1)	100 ft coil
1/2 in.	0.524 (13.3)	0.500 (12.7)	100 ft coil
5/8 in.	0.655 (16.6)	0.625 (15.9)	50 ft coil
3/4 in.	0.786 (20.0)	0.750 (19.1)	50 ft coil
7/8 in.	0.911 (23.1)	0.875 (22.2)	50 ft coil
1 in.	1.036 (26.3)	1.000 (25.4)	50 ft coil

Wall Thickness Grade A: 0.040±0.016 inch (1.0±0.4mm)

Grade B: 0.031±0.016 inch (0.8±0.4mm)

Grade C: 0.028±0.016 inch (0.7±0.4mm)

Applies only to sizes under 1/2in.

Sleeving 1/2in and above may have thicker wall